

HL-WP Series

STAINLESS STEEL, WASHDOWN DIGITAL SCALES

Ideal for harsh environment applications, such as food processing, foodservice, chemical and outdoor use.

Portable
(battery powered)

g / lb / lb-oz
Mode Selection
(varies with model)



*HL-WP Models
(5" square pans)*

*HL-LWP Models
(5.4" x 6.8" pans)*

NSF Certified



NTEP Approved
(some models)



Features

- Low Battery Indication Auto Power Off (5 min.) to preserve battery life
- Choice of 2 sizes of removable stainless steel pans
- Re-Zero (tare) Function
- Resolution up to 3,000 divisions
- HL-3000 WPN & HL-3000LWPN (NTEP Approved)
- Temperature Compensated
- Full Scale Pushbutton Tare/Zero
- AC Adapter (option)
- 2 Year Warranty

Models with 5" Square Weigh Pans

HL-WP Series	gram Mode		lb Mode		lb / oz Mode		oz Mode	
	Capacity	Resolution	Capacity	Resolution	Capacity	Resolution	Capacity	Resolution
HL-300WP	300 g	0.1 g	-	-	-	-	10.58 oz	0.01 oz
HL-1000WP	1000 g	0.5 g	2.2 lb	0.001 lb	2 lb, 3.3 oz	0.1 oz	35.28 oz	0.02 oz
HL-3000WP	3000 g	1 g	6.6 lb	0.002 lb	6 lb, 9.8 oz	0.1 oz	105.8 oz	0.1 oz
HL-3000WPN	3000 g	1 g	6.6 lb	0.002 lb	-	-	105.8 oz	0.1 oz

Models with Larger 5-3/8" Deep x 6-3/4" Wide Weigh Pans

HL-WP Series	gram Mode		lb Mode		lb / oz Mode		oz Mode	
	Capacity	Resolution	Capacity	Resolution	Capacity	Resolution	Capacity	Resolution
HL-3000LWP	3000 g	1 g	6.6 lb	0.002 lb	6 lb, 9.8 oz	0.1 oz	105.8 oz	0.1 oz
HL-3000LWPN	3000 g	1 g	6.6 lb	0.002 lb	-	-	105.8 oz	0.1 oz

Fax-on-Demand

(800) 726-7099, Press 2 / (408) 263-2278

Document #1011

www.andweighing.com



1555 McCandless Drive
Milpitas, CA 95035, USA
Toll Free: (800) 726-7099
Phone: (408) 263-5333
Fax: (408) 263-0119

HL-WP Series Specifications

	HL-300WP	HL-1000WP	HL-3000WP	HL-3000WPN	HL-3000LWP	HL-3000LWPN
Grams (g)	300 x 0.1 g	1000 x 0.5g	3000 x 1g	3000 x 1g	3000 x 1g	3000 x 1g
Pounds (lb)	-	2.2 x 0.001 lb	6.6 x 0.002 lb	6.6 x 0.002 lb	6.6 x 0.002 lb	6.6 x 0.002 lb
Pounds / ounces (lb / oz)	-	2 lb, 3.3 oz x 0.1 oz	6 lb, 9.8 oz x 0.1 oz	-	6 lb, 9.8 oz x 0.1 oz	-
Ounces (oz)	10.58 x 0.01 oz	35.28 x 0.02 oz	105.8 x 0.1 oz	105.8 x 0.1 oz	105.8 x 0.1 oz	105.8 x 0.1 oz
Weigh Pan Size	128 mm / 5" square				170 x 137 mm / 6.8 x 5.4" (w x d)	
Linearity	0.1 g	0.5 g	1 g			
Repeatability/ Std. Deviation	0.1 g	0.5 g	1 g			

All Models	
Display	12mm/ 0.5 inch, 7 segment LCD
Dimensions	63 (H) x 170 (W) x 220 (D) mm / 2.5 (H) x 6.68 (W) x 6.84 (D) inches
Power	6 'AA' size batteries (not included) or FV-05 AC adapter (option)
Battery Life	Approx. 100 hours (manganese type), 200 hours (alkaline at 20° C / 68° F)
Operating Temp.	-10°C~40°C / 14°F~104°F RH less than 85%
Weight	Approx. 870 g. / 2 lb

Specifications are subject to change without notice.

Options:

- FV-05 AC Adapter (110VAC) – power transformer is not waterproof
- FV-06 AC Adapter (220VAC) – power transformer is not waterproof

Fax-on-Demand

(800) 726-7099, Press 2 / (408) 263-2278

Document #1011

www.andweighing.com



1555 McCandless Drive
 Milpitas, CA 95035, USA
 Toll Free: (800) 726-7099
 Phone: (408) 263-5333
 Fax: (408) 263-0119