



OHAUS raises the bar in price-performance ratio with the newly-designed Navigator series which is perfect for general weighing applications in laboratory, industrial and education settings. Ruggedly constructed and multifunctional, the Navigator's a powerful balance that can handle a diverse range of weighing applications with features such as fast stabilization time, overload protection at four times its rated capacity, and easy operation.

Applications

Weighing, Parts Counting, Percent Weighing, Checkweighing

Display

Liquid Crystal Display (LCD) with backlight

Operation

AC adapter (included) or 4 C batteries (not included)

Communication

RS232, USB, or Ethernet (available as accessories)

Construction

ABS housing, stainless steel pan, transportation lock, slip-resistant and adjustable feet, leveling bubble

Design Features

Menu and calibration lock switch, mechanical and software overload/underload protection, stability indicator, low battery indicator, auto shut-off, user-selectable print options, user-selectable communication settings

SPECIFICATIONS

Maximum Capacity	620 g
Readability	0.01 g
Pan Size	5.7 in (145 mm)
Battery Life	270 Hours with Disposable Batteries
Communication	RS232 (Available as an Accessory); USB (Available as an Accessory)
Dimensions	2.8 in x 9.1 in x 8 in (70 mm x 230 mm x 204 mm)
Display	LCD Display with white backlight
In-use cover	No
Legal for Trade	Not Applicable
Net Weight	2.2 lb (1 kg)
Pan Construction	Stainless Steel

Power	4 C (LR14) Batteries (Not Included); AC Adapter (Included)
Stabilization Time	1.5 s
Tare Range	To capacity by subtraction
Transportation Case	Available as an Accessory
Units of Measurement	Carat; Grain; Gram; Newton; Ounce; Ounce Troy; Pennyweight
Working Environment	50°F – 104°F, 85%RH, non-condensing (10°C – 40°C, 85%RH, non-condensing)
Auxiliary Display Model	Not Applicable
